

18-26.5GHz 1W Power Amplifier

P/N: MZPA18265GA1W



■ Features

- Ultra Wide Band: 18-26.5GHz
- Gain: 21dB
- Output Power Psat: 30dBm
- Bias: Vd=12V;Id=0.6A

■ Applications

- Radar Systems
- Communication Systems
- Receivers Systems

■ Electrical Specifications +25 °C



Parameter	Min.	Typ.	Max	Units
Frequency Range	18-26.5			GHz
Small Signal Gain		21		dB
Gain Flatness		±2.0		dB
Input VSWR		2.0		-
Output VSWR		2.0		-
Output Power for 1 dB Compression (P1dB)		29		dBm
Saturated Output Power (Psat)		30		dBm
Spurious		-60		dBc
Input Max Power(no damage)			+15	dBm
DC Current (Vcc=+12V)		500	800	mA
Impedance	50			Ω
Input Output Connector	2.92mm-Female			
Material /Finishing	Aluminium/Gold Painting			
Weight	200g			
Package Sealing	General Sealing (Standard)			

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com

18-26.5GHz 1W Power Amplifier

P/N: MZPA18265GA1W



■ Environmental Conditions

Operational Temperature	-45°C~+85°C	Vibration	25g rms (15 degree 2KHz) endurance, 1 hour per axis
Storage Temperature	-55°C~+125°C	Shock	20G for 11msc half sin wave, 3 axis both directions
Executive Standard	MIL-STD-810G	Humidity	100% RH at 35c, 95%RH at 40°C


■ Absolute Maximum Ratings

Supply Bias Voltage	+15V
RF INPUT POWER	15dBm
ESD sensitivity (HBm)	Class 0, passed 150V



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com