

0.1-40GHz Low Noise Amplifier

P/N: LNA00140GA14



Description:

The amplifier is a low noise amplifier with a small signal gain of 15 dB and a typical noise figure of 4.5 dB across the frequency range of 0.1 to 40GHz. The typical output power P-1 is 20 dBm. The DC power requirement for the amplifier is +12 VDC/280mA. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		0.1-40		GHz
Gain	15	17		dB
Gain Flatness			±3.0	dB
Input VSWR		1.5	2.0	-
Output VSWR		1.5	2.0	-
Output Power for (P1dB)	18	20		dBm
Output Power Past		21		dBm
OIP3		30		dBm
Noise Figure		4.5	6	dB
Input Max Power(no damage)			+5	dBm
DC Current(Vcc=+12V)		280		mA
Impedance		50		Ω
Input/Output Connector		2.92-k		
Material		Aluminium/Gold Plated		
Weight		/		
Package Sealing		General Sealing (Standard)		

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


0.1-40GHz Low Noise Amplifier

P/N: LNA00140GA14



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com