

0.1-40GHz Low Noise Amplifier

P/N: LNA00140GA27



Description:

The amplifier is a low noise amplifier with a typical small signal gain of 27 dB and a typical noise figure of 6 dB across the frequency range of 0.01 to 40GHz. The typical output power P-1 21dBm. The DC power requirement for the amplifier is +12 VDC/300 mA. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		0.1-40		GHz
Gain	26	28		dB
Gain Flatness		±1.5	±2	dB
Input VSWR		2	2.4	-
Output VSWR		2	2.4	-
Output Power for (P1dB)	17	19		dBm
Output Power Past		20		dBm
OIP3		30		dBm
Noise Figure		4.5	6	dB
Input Max Power(no damage)			0	dBm
DC Current(Vcc=+12V)		400		mA
Impedance		50		Ω
Input/Output Connector		2.92mm-Female		
Material		Aluminium/Gold Plated		
Weight		/		
Package Sealing		General Sealing (Standard)		

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


0.1-40GHz Low Noise Amplifier

P/N: LNA00140GA27



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com