

# 1-18GHz Low Noise Amplifier

P/N: LNA0118GAC48



## Description:

The amplifier is a low noise amplifier with a typical small signal gain of 50 dB and a typical noise figure of 2 dB across the frequency range of 1 to 18 GHz. The typical output power P-1 21dBm. The AC power requirement for the amplifier is 220 VAC/50 mA. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

## Electrical Specifications ( +25°C ) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		1-18		GHz
Gain	48	50		dB
Gain Flatness		±2		dB
Input VSWR		1.7	2.0	-
Output VSWR		1.7	2.0	-
Output Power for (P1dB)	20	21		dBm
Output Power Psat		22		dBm
Spurious		-60		dBc
Noise Figure		2		dB
Output IP3		32		dBm
Input Max Power(no damage)			-20	dBm
AC		110~220/50Hz		VAC
Impedance		50		Ω
Input/Output Connector		SMA-Female/SMA-Female		
Material		Aluminium		
Weight		800g		
Package Sealing		General Sealing (Standard)		

## Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE  
PRECAUTIONS ELECTROSTATIC  
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


# 1-18GHz Low Noise Amplifier

P/N: LNA0118GAC48



## ■ Outline Drawing

All Dimensions in mm (inches) Tolerance  $\pm 0.25$  (0.01)



**\*\*\*Heat Sink required during operation\*\*\***

### NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

**MICZEN THCHNOLOGIES CO.,LTD.**

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com