

4-18GHz Low Noise Amplifier

P/N: LNA040180GA34



Description:

The amplifier is a low noise amplifier with a typical small signal gain of 34 dB and a typical noise figure of 3.5 dB across the frequency range of 4 to 18 GHz. The typical output power P-1 27dBm. The DC power requirement for the amplifier is +12 VDC/900 mA. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		4-18		GHz
Gain	34			dB
Gain Flatness			±1.0	dB
Gain varies with temperature		0.03		dB/°C
Input VSWR			1.5	-
Output VSWR		2.0		-
Output Power for (P1dB)	27			dBm
Output Power Psat		28		dBm
Spurious		-60		dBc
Noise Figure		3.5	4	dB
Input Max Power(no damage)			0	dBm
DC Voltage	+12		+15	V
DC current@+15V		900		mA
Impedance		50		Ω
Input/Output Connector		SMA-Female/SMA-Female		
Material		Aluminium\Gold Painting		
Weight		-		
Package Sealing		General Sealing (Standard)		

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


4-18GHz Low Noise Amplifier

P/N: LNA040180GA34



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:


1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com

4-18GHz Low Noise Amplifier

P/N: LNA040180GA34



■ Performance Plot

