

0.9-6GHz Low Noise Amplifier

P/N: MZLNA00906GA35



Description:

The amplifier is a low noise amplifier with a typical small signal gain of 35 dB and a typical noise figure of 1.5 dB across the frequency range of 0.9 to 6GHz. The typical output power P-1 15dBm. The DC power requirement for the amplifier is +12VDC/500 mA. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		0.9-6		GHz
Gain		35		dB
Gain Flatness		±1		dB
Input VSWR			1.5	-
Output VSWR			1.5	-
Output Power for (P1dB)	15			dBm
Noise Figure			1.5	dB
Impedance		50		Ω
Input/Output Connector		SMA-Female/SMA-Female		
Material		Aluminum/Gold Painting		
Weight		-		
Package Sealing		General Sealing (Standard)		

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com

0.9-6GHz Low Noise Amplifier

P/N: MZLNA00906GA35



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)

*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com