

2-4GHz Low Noise Amplifier

P/N: MZLNA0204GC23



Description:

The amplifier is a low noise amplifier with a typical small signal gain of 26 dB and a typical noise figure of 0.7 dB across the frequency range of 2 to 4 GHz. The typical output power P-1 20dBm. The DC power requirement for the amplifier is +12 VDC/200 mA. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		2-4		GHz
Gain	23		26	dB
Gain Flatness		±1.0	±1.5	dB
Input VSWR		1.8	2.2	-
Output VSWR		1.8	2.0	-
Output Power for (P1dB)	18	20		dBm
Output Power Psat		21		dBm
Noise Figure		0.7	1	dB
Spurious		-60		dBc
Output IP3	32	36		dBm
Input Max Power(no damage)			0	dBm
Reverse Isolation	25	50		dB
DC Current (Vcc=+12V)		150	200	mA
Impedance		50		Ω
Input/Output Connector	SMA-Female/SMA-Female			
Material	Aluminium			
Weight	50g			
Package Sealing	General Sealing (Standard)			

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


2-4GHz Low Noise Amplifier

P/N: MZLNA0204GC23



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.


Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com

2-4GHz Low Noise Amplifier

P/N: MZLNA0204GC23



Performance Plot



MICZEN THCNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com