

18-26GHz Low Noise Amplifier

P/N: MZLNA1826GA30



Description:

The amplifier is a low noise amplifier with a typical small signal gain of 32 dB and a typical noise figure of 2.5 dB across the frequency range of 18 to 26 GHz. The typical output power P-1 15dBm. The DC power requirement for the amplifier is +12 VDC/260 mA. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		18-26		GHz
Gain	30	32		dB
Gain Flatness		±1.5	±2	dB
Input VSWR		1.5	2.0	-
Output VSWR		1.8	2.0	-
Output Power for (P1dB)	13	15		dBm
Output Power Psat		15		dBm
Noise Figure		1.5	2.0	dB
Output IP3		24		dBm
Input Max Power(no damage)			-5	dBm
DC Current (Vcc=+12V)		260		mA
Impedance		50		Ω
Input/Output Connector		SMA-Female/SMA-Female		
Material		Aluminium/Gold Painting		
Weight		93g		
Package Sealing		General Sealing (Standard)		

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


18-26GHz Low Noise Amplifier

P/N: MZLNA1826GA30



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCNOLOGIES CO.,LTD.


Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com

18-26GHz Low Noise Amplifier

P/N: MZLNA1826GA30



Performance Plot



MICZEN THCNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com