

20-34GHz Low Noise Amplifier

P/N: MZLNA2034GA40



Description:

The amplifier is a low noise amplifier with a typical small signal gain of 45 dB and a typical noise figure of 1.8 dB across the frequency range of 20 to 34 GHz. The typical output power P-1 20dBm. The DC power requirement for the amplifier is +12 VDC/260 mA. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		20-34		GHz
Gain	40	45		dB
Gain Flatness		±2.0		dB
Input VSWR		1.8		-
Output VSWR		1.8		-
Output Power for (P1dB)		20		dBm
Output Power Psat		22		dBm
Output IP3		30		dBm
Noise Figure		1.8	2.8	dB
Input Max Power(no damage)			-15	dBm
DC Current (Vcc=+12V)		200	260	mA
Impedance		50		Ω
Input/Output Connector	2.92mm-Female/2.92mm-Female			
Material	Aluminium			
Weight	30g			
Package Sealing	General Sealing (Standard)			

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


20-34GHz Low Noise Amplifier

P/N: MZLNA2034GA40



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com