

1-5GHz 2way Power Divider

P/N: MZP20105GA



Description:

The power divider is a 2way power divider with a typical insertion loss of 0.45 dB and a typical isolation of 20dB across the frequency range of 1 to 5 GHz. The power divider can reach handling power 30W. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		1-5		MHz
Insertion Loss		0.45	0.6	dB
Isolation	20			dB
Input VSWR			1.3	-
Output VSWR			1.2	-
Phase Unbalance			±3	°
Amplitude Unbalance			±0.3	dB
Forward Power Handle Capability		30		W
Reverse Power Handle Capability		2		W
Impedance		50		Ω
Connector		SMA-Female		
Material		Aluminum		
Weight		18g		
Package Sealing		Blue Color(Standard)		

Environmental Specifications:

- ※ Operational Temperature -45°C~+85°C
- ※ Storage Temperature -55°C~+105°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


1-5GHz 2way Power Divider

P/N: MZP20105GA



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCNOLOGIES CO.,LTD.


Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com

1-3GHz 2way Power Divider

P/N: MZP20103GA



Performance Plot



MICZEN THCNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com