


18-26.5GHz 2way Power Divider

P/N: MZP2180265GC



Description:

The power divider is a 2way power divider with a typical insertion loss of 0.5 dB and a typical isolation of 19dB across the frequency range of 18 to 26.5 GHz. The power divider can reach handling power 10W. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		18-26.5		GHz
Insertion Loss		0.5	0.8	dB
Isolation	18	19		dB
Input VSWR			1.5	-
Output VSWR			1.4	-
Phase Unbalance			±4	°
Amplitude Unbalance			±0.3	dB
Power Handling			10	W
Impedance		50		Ω
Connector		2.92-Female		
Material		Aluminum		
Weight		-g		
Package Sealing		Blue Color(Standard)		

Environmental Specifications:

- ※ Operational Temperature -45°C~+85°C
- ※ Storage Temperature -55°C~+105°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


18-26.5GHz 2way Power Divider

P/N: MZP2180265GC



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.


Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com

18-26.5GHz 2way Power Divider

P/N: MZP2180265GC



Performance Plot



MICZEN THCNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com