

1-18GHz Power Amplifier

P/N: MZPA0118GA25



Description:

The power amplifier is a power amplifier with a typical small signal gain of 25 dB across the frequency range of 1 to 18 GHz. The typical output power P-1 27dBm. The DC power requirement for the amplifier is +12 VDC/0.5 A. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		1-18		GHz
Gain	20	25		dB
Gain Flatness		±3		dB
Input VSWR		1.5	2.0	-
Output VSWR		1.8	2.0	-
Noise Figure		5		dB
Second Harmonic		-15	-13	dBc
Output Power for (P1dB)	26	27		dBm
Output Power Psat	28			dBm
OIP3		40		-
Spurious		-60		dBc
Input Max Power(no damage)			10	dBm
DC Current (Vcc=+12V)		0.5		A
Impedance		50		Ω
Input/Output Connector	SMA-Female/SMA-Female			
Material	Aluminium/Conductive oxide			
Weight	50g			
Package Sealing	General Sealing (Standard)			

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


1-18GHz Power Amplifier

P/N: MZPA0118GA25



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com