

18-25GHz 3W Power Amplifier

P/N: MZPA1825GA3W



Description:

The power amplifier is a 3W power amplifier with a typical small signal gain of 34 dB across the frequency range of 18 to 25 GHz. The typical output power P-1 34dBm. The DC power requirement for the amplifier is +12 VDC/3 A. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		18-25		GHz
Gain	35			dB
Gain Flatness		±1.5	±2.0	dB
Input VSWR		1.8	2.0	-
Output VSWR		2.0	2.9	-
Output Power for (P1dB)	33.5	34		dBm
Output Power Psat	34.5			dBm
Input Max Power(no damage)			10	dBm
DC Current (Vcc=+12V)(@Pout=3W)		2.3	3	A
Impedance		50		Ω
Input/Output Connector		SMA-K/SMA-K		
Material		Aluminium/Gold Plating		
Weight		-		
Package Sealing		General Sealing (Standard)		

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


18-25GHz 3W Power Amplifier

P/N: MZPA1825GA3W



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com