


# 24.9-25.1GHz 2W Power Amplifier

P/N: MZPA24902510GA2W-SR



## Description:

The power amplifier is a 2W power amplifier with a typical small signal gain of 40 dB across the frequency range of 24.9 to 25.1 GHz. The typical output power P-1 33dBm. The DC power requirement for the amplifier is +11~18 VDC/2 A. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

## Electrical Specifications ( +25°C ) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		24.9-25.1		GHz
Gain	40			dB
Gain Flatness		±0.4	±0.6	dB
Input VSWR			2.0	-
Output VSWR			2.0	-
Output Power for (P1dB)	33			dBm
Output Power Psat		34		dBm
Noise Figure		6		dB
Spurious		-60		dBc
OIP3		40		dBm
Input Max Power(no damage)			0	dBm
DC Current(Vcc=+11-18V) (@Pout=2W)		2		A
Impedance		50		Ω
Input/Output Connector		2.92mm-K/2.92mm-K		
Material		Aluminium\Gold Painting		
Weight		-		
Package Sealing		General Sealing (Standard)		

## Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE  
PRECAUTIONS ELECTROSTATIC  
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


# 24.9-25.1GHz 2W Power Amplifier

P/N: MZPA24902510GA2W-SR



## ■ Outline Drawing

All Dimensions in mm (inches) Tolerance  $\pm 0.25$  (0.01)



**\*\*\*Heat Sink required during operation\*\*\***

### NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

**MICZEN THCHNOLOGIES CO.,LTD.**

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com