


1-18GHz 1W Power Amplifier

P/N: PA0118GD1W



Description:

The power amplifier is a 1W power amplifier with a typical small signal gain of 40 dB across the frequency range of 1 to 18 GHz. The typical output power P-1 30.5dBm. The DC power requirement for the amplifier is +18 VDC/1 A. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		1-18		GHz
Gain	40			dB
Gain Flatness		±2.0	±2.5	dB
Input VSWR		2.0	2.2	-
Output VSWR		2.0	2.2	-
Noise Figure			3	dB
Output Power for (P1dB)	30	30.5		dBm
Output Power Psat		31		dBm
Spurious		60		dBc
Input Max Power(no damage)			5	dBm
DC Current (Vcc=+18V)(@P1dB)			1	A
Impedance		50		Ω
Input/Output Connector		SMA-Female/SMA-Female		
Material		Aluminium/Gold Plating		
Weight		75g		
Package Sealing		General Sealing (Standard)		

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


1-18GHz 1W Power Amplifier

P/N: PA0118GD1W



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com