


18-40GHz 7W Power Amplifier

P/N: PA1840GB7W-SR



Description:

The power amplifier is a 7W power amplifier with a typical small signal gain of 45 dB across the frequency range of 18 to 40 GHz. The typical output power P-1 is 39dBm. The DC power requirement for the amplifier is +28 VDC/5 A. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		18-40		GHz
Gain	45			dB
Gain Flatness		±2.5		dB
Input VSWR		2.0		-
Output Power for (P _{sat})		39		dBm
Input Max Power(no damage)			0	dBm
DC Current (V _{cc} =+28V)(@P _{out} =7W)		5		A
Impedance		50		Ω
Input/Output Connector	2.92mm-Female/2.92mm-Female			
Material	Aluminium/Sliver Plating			
Heatsink	Option			
Weight	1500g			
Package Sealing	General Sealing (Standard)			

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


18-40GHz 7W Power Amplifier

P/N: PA1840GB7W-SR



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com