

23-25GHz 10W Power Amplifier

P/N: PA2325GA10W-SR



Description:

The power amplifier is a 10W power amplifier with a typical small signal gain of 40 dB across the frequency range of 23 to 25 GHz. The typical output power P-1 38dBm. The DC power requirement for the amplifier is +28 VDC/5 A. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

Electrical Specifications (+25°C) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		23-25		GHz
Power Gain	40			dB
Power Gain Flatness		±1.5	±2	dB
Input VSWR		2.0		-
Output Power for (P1dB)		38		dBm
Output Power Psat	40			dBm
Spurious		-60		dBc
Input Max Power(no damage)			5	dBm
DC Current (Vcc=+28V)(@Pout=10W)		4	5	A
Impedance		50		Ω
Input/Output Connector		2.92-Female/2.92-Female		
Material		Aluminium		
Weight		-		
Package Sealing		General Sealing (Standard)		

Environmental Specifications:

- ※ Operational Temperature -25°C~+85°C
- ※ Storage Temperature -55°C~+125°C



OBSERVE
PRECAUTIONS ELECTROSTATIC
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


23-25GHz 10W Power Amplifier

P/N: PA2325GA10W-SR



■ Outline Drawing

All Dimensions in mm (inches) Tolerance ± 0.25 (0.01)



*****Heat Sink required during operation*****

NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com