

# 0.8-2.5GHz 16way Power Divider

P/N: QLP160080250GA



## Description:

The power divider is a 16way power divider with a typical insertion loss of 1.2dB and a typical isolation of 18dB across the frequency range of 0.8 to 2.5 GHz. The power divider can reach handling power 30W. Accept customization according to different needs.



- Radar Systems
- Communication Systems
- Receivers Systems

## Electrical Specifications ( +25°C ) :

Parameter	Min.	Typ.	Max.	Units
Frequency Range		0.8-2.5		GHz
Insertion Loss			1.2	dB
Isolation	18			dB
Input VSWR			1.6	-
Output VSWR			1.4	-
Phase Unbalance			±6	°
Amplitude Unbalance			±0.6	dB
Power Handling		30		W
Impedance		50		Ω
Input/Output Connector		N-Female		
Material		Aluminum		
Weight		-g		
Package Sealing		Black Color(Standard)		

## Environmental Specifications:

- ※ Operational Temperature -45°C~+85°C
- ※ Storage Temperature -55°C~+105°C



OBSERVE  
PRECAUTIONS ELECTROSTATIC  
SENSITIVE DEVICES

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com


# 0.8-2.5GHz 16way Power Divider

P/N: QLP160080250GA



## ■ Outline Drawing

All Dimensions in mm (inches) Tolerance  $\pm 0.25$  (0.01)



### NOTE:

1. The product is designed to meet environmental ratings but not tested. If you need to test environmental condition, please contact our sales department.
2. Miczen technologies co., Ltd. reserves the right to change the above information without notice.

MICZEN THCHNOLOGIES CO.,LTD.

Phone: +86 28 65003621 | E-mail: sales@miczen.com | Web: www.miczen.com